

#### SAFETY DATA SHEET

## JLM Petrol Hybrid Treatment 250ml

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Trade name

JLM Petrol Hybrid Treatment 250ml

Product no.

J03195

Unique formula identifier (UFI)

GAU8-P0QG-P006-4G9R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Additive

Use descriptors (REACH)

**Product category** 

Description

Additives to petrol or diesel fuel

#### Uses advised against

None known.

## 1.3. Details of the supplier of the safety data sheet

## Company and address

## JLM Lubricants BV

Schiphol Boulevard 127

1118 BG Schiphol

Netherlands

+31 (0)20 2014995

www.jlmlubricants.com

## Contact person

**Product Safety Department** 

#### E-mail

info@jlmlubricants.com

## Revision

31/05/2023

## **SDS Version**

3.0

## Date of previous version

24/01/2023 (2.0)

## 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

## 2.2. Label elements

Hazard pictogram(s)

Hybrid Protect and Clean Page 1 of 19





## Signal word

Danger

## Hazard statement(s)

May be fatal if swallowed and enters airways. (H304) Harmful to aquatic life with long lasting effects. (H412)

## Precautionary statement(s)

## General

Keep out of reach of children. (P102)

## Prevention

Avoid release to the environment. (P273)

#### Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)

Do NOT induce vomiting. (P331)

## Storage

-

## Disposal

Dispose of contents/container in accordance with local regulation. (P501)

## Hazardous substances

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C10, aromatics, > 1% naphthalene

Diethylbenzene

## Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

UFI: 790K-74EH-000N-5T5Q

## 2.3. Other hazards

## Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

Not applicable. This product is a mixture.

## 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, <2% aromatics	CAS No.: EC No.: 918-481-9 UK-REACH: Index No.:	80-95%	EUH066 Asp. Tox. 1, H304	
Hydrocarbons, C10, aromatics, > 1% naphthalene	CAS No.: EC No.: 919-284-0 UK-REACH: Index No.:	1-3%	EUH066 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	
Polyolefin alkyl phenol alkyl amine	CAS No.: EC No.: UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315	
Alkaryl polyether	CAS No.: EC No.: UK-REACH: Index No.:	1-3%	Aquatic Chronic 3, H412	



1,2,4-trimethylbenzene	CAS No.: 95-63-6 EC No.: 202-436-9 UK-REACH: Index No.: 601-043-00-3	<1%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
2,6-di-tert-butylphenol	CAS No.: 128-39-2 EC No.: 204-884-0 UK-REACH: Index No.:	<1%	Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
2-ethylhexan-1-ol	CAS No.: 104-76-7 EC No.: 203-234-3 UK-REACH: Index No.:	<1%	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	[1]
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5 UK-REACH: Index No.: 601-052-00-2	<1%	Flam. Sol. 2, H228 Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
mesitylene;1,3,5- trimethylbenzene	CAS No.: 108-67-8 EC No.: 203-604-4 UK-REACH: Index No.: 601-025-00-5	<1%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
Diethylbenzene	CAS No.: 25340-17-4 EC No.: 246-874-9 UK-REACH: Index No.:	<1%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
propylbenzene;cumene	CAS No.: 98-82-8 EC No.: 202-704-5 UK-REACH: Index No.: 601-024-00-X	<0.05%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Carc. 2, H351 Aquatic Chronic 2, H411	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

## Other information

[1] European occupational exposure limit.

#### SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

## Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

## Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.



#### Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

## Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

#### Burns

Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (naphthalene)

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

## 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

## 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

## 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

## 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

## 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.



## 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## Recommended storage material

Keep only in original packaging.

## Storage temperature

Dry, cool and well ventilated

Store out of direct sunlight.

## Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

## 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

## 8.1. ▼ Control parameters

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Long term exposure limit (8 hours) (ppm): 184 Long term exposure limit (8 hours) (mg/m³): 1200

2-ethylhexan-1-ol

Long term exposure limit (8 hours) (ppm): 1 Long term exposure limit (8 hours) (mg/m³): 5,4

propylbenzene;cumene

Long term exposure limit (8 hours) (ppm): 25 Long term exposure limit (8 hours) (mg/m³): 125

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m³): 250

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

## **▼** DNEL

## 1,2,4-trimethylbenzene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	9512 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	16171 mg/kg bw/day
Long term – Local effects - General population	Inhalation	29.4 mg/m³
Long term – Local effects - Workers	Inhalation	100 mg/m³
Long term – Systemic effects - General population	Inhalation	29.4 mg/m³
Long term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	29.4 mg/m³
Short term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	29.4 mg/m³
Short term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	15 mg/kg bw/day

## 2-ethylhexan-1-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	11.4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	23 mg/kg bw/day
Long term – Local effects - General population	Inhalation	26.6 mg/m <sup>3</sup>



cording to Ec-Negalation 1907/2000 (NEACH), annex II, including	changes implemented by Ec-Regulation	2020/070 jml.bricarts.com
Long term – Local effects - Workers	Inhalation	53.2 mg/m³
Long term – Systemic effects - General population	Inhalation	2.3 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	12.8 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	26.6 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	53.2 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	1.1 mg/kg bw/day
naphthalene		
Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	3,57 mg/kgbw/day
Long term – Systemic effects - Workers	Inhalation	25 mg/m³
propylbenzene;cumene		
Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1.2 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	15.4 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	16.6 mg/m³
Long term – Systemic effects - Workers	Inhalation	100 mg/m³
Short term – Local effects - Workers	Inhalation	250 mg/m³
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day
PNEC 1,2,4-trimethylbenzene		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		120 μg/L
Freshwater sediment		13.56 mg/kg
Intermittent release (freshwater)		120 μg/L
Marine water		120 μg/L
Marine water sediment		13.56 mg/kg
Sewage treatment plant		2.41 mg/L
Soil		2.34 mg/kg
2-ethylhexan-1-ol		
B. 1	e=	

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		17 μg/L
Freshwater sediment		284 μg/kg
Intermittent release (freshwater)		170 μg/L
Marine water		1.7 μg/L
Marine water sediment		28.4 μg/kg
Predators		55 mg/kg
Sewage treatment plant		10 mg/L
Soil		47 μg/kg

## naphthalene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,0024 mg/L
Marine water		0,0024 mg/L

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.



#### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

## Exposure scenarios

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

## Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

## Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

## Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment

#### Generally

Use only UKCA marked protective equipment.

## Respiratory Equipment

## Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	R



Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,38	> 240	EN374-2, EN374-3, EN388	



## Eye protection **Type**

Safety glasses with side	EN166
shields.	



## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

**Standards** 

Physical state

Liquid

Colour

Tan

Odour / Odour threshold

Characteristic

рΗ

Testing not relevant or not possible due to nature of the product.

Density (q/cm<sup>3</sup>)

0.797 (20 °C)

Kinematic viscosity



No data available

Particle characteristics

Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

>150

Vapour pressure

No data available

Relative vapour density

No data available

Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

▼ Flash point (°C)

>61

Flammability (°C)

No data available

Auto-ignition temperature (°C)

No data available

Lower and upper explosion limit (% v/v)

No data available

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

No data available

Solubility in fat (g/L)

No data available

9.2. Other information

Evaporation rate (n-butylacetate = 100)

No data available

Other physical and chemical parameters

No data available.

▼ Oxidizing properties

No data available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



▼ Acute toxicity

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Test method: OECD 403
Species: Rat
Route of exposure: Inhalation
Test: LC50 (4 hours)
Result: >5000 mg/m³

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Test method: OECD 401
Species: Rat
Route of exposure: Oral
Test: LD50
Result: >5000 mg/kg

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Test method: OECD 402
Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >5000 mg/kg

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Test method: OECD 403
Species: Rat
Route of exposure: Inhalation
Test: LC50 (dust)
Result: >4778 mg/m³

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Test method: OECD 403
Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: >4688 mg/m³

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Test method: OECD 402
Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Test method: OECD 401
Species: Rat
Route of exposure: Oral
Test: LD50
Result: 6318 mg/kg

Product/substance Polyolefin alkyl phenol alkyl amine

Test method: OECD 402
Species: Rat
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg

Product/substance Polyolefin alkyl phenol alkyl amine

Test method: OECD 423
Species: Rat
Route of exposure: Oral
Test: LD50
Result: >5000 mg/kg



Product/substance Alkaryl polyether

Species:

Rabbit Dermal

Route of exposure: Test:

LD50

Result:

>3000 mg/kg

Product/substance

Alkaryl polyether

Test method: Species:

OECD 423 Rat

Route of exposure: Test:

Oral LD50

Result:

>2000 mg/kg

Product/substance

1,2,4-trimethylbenzene

Species:

Route of exposure: Test:

Inhalation LC50

Result:

10200 mg/m<sup>3</sup>

Product/substance

1,2,4-trimethylbenzene

Species:

Dermal

Route of exposure: Test: Result:

LD50 >3440 mg/kg

Product/substance Test method: Species:

naphthalene **OECD 403** Rat Inhalation

Route of exposure: Test: Result:

LC50 >0,4 mg/L

Product/substance Test method: Species:

naphthalene **OECD 402** Rat Dermal

Route of exposure:

LD50

Test: Result:

>16000 mg/kg

Product/substance Test method:

naphthalene **OECD 401** Mouse Oral

Route of exposure: Test: Result:

Species:

LD50 533 mg/kg

Product/substance

mesitylene;1,3,5-trimethylbenzene

Species:

Route of exposure:

Rat

Test: Result: LC50 10,2 mg/L

Product/substance Route of exposure: mesitylene;1,3,5-trimethylbenzene

Species:

Rat Dermal LD50 >3440 mg/kg

Test: Result:

Species:

Result:

Product/substance

mesitylene;1,3,5-trimethylbenzene Rat Oral

Route of exposure: Test:

LD50 >5000 mg/kg



Product/substance Diethylbenzene

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >5000 mg/kg

Product/substance Diethylbenzene

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 2050 mg/kg

Product/substance propylbenzene;cumene

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >10000 mg/kg

Product/substance propylbenzene;cumene

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 2260 mg/kg

▼ Skin corrosion/irritation

Product/substance Polyolefin alkyl phenol alkyl amine Test method: OECD 404

Test method: OECD 40 Species: Rabbit Duration:

Result: Adverse effect observed (Irritating)

Product/substance 1,2,4-trimethylbenzene

Species: Rabbit Duration:

Result: Adverse effect observed (Irritating)

Product/substance mesitylene;1,3,5-trimethylbenzene

Species: Rabbi Duration:

Result: Adverse effect observed (Irritating)

Product/substance Diethylbenzene
Test method: OECD 404
Species: Rabbit

Duration:

Result: Adverse effect observed (Irritating)

▼ Serious eye damage/irritation

Product/substance mesitylene;1,3,5-trimethylbenzene

Test method: OECD 405 Species: Rabbit

Duration:

Result: Adverse effect observed (Irritating)

Product/substance Diethylbenzene

Species: Rabbit Duration:

Result: Adverse effect observed (Slightly irritating)

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity



Based on available data, the classification criteria are not met.

**▼** Carcinogenicity

Product/substance naphthalene Species: Rat Route of exposure: Inhalation

Target organ:

Duration: 24 months Test: NOAEL

Result:

Conclusion: Adverse effect observed

Product/substance propylbenzene;cumene

Test method: OECD 451
Species: Rat
Route of exposure: Inhalation
Target organ:
Duration: 24 months

Test:

Conclusion:

Result:

▼ Reproductive toxicity

Product/substance Polyolefin alkyl phenol alkyl amine

Adverse effect observed

Test method: OECD 421 Species: Rat, female

Duration: Test: Result:

Conclusion: Adverse effect observed

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

None known.

▼ Endocrine disrupting properties

Not applicable.

Other information

naphthalene has been classified by IARC as a group 2B carcinogen.

propylbenzene; cumene has been classified by IARC as a group 2B carcinogen.

## **SECTION 12: Ecological information**

12.1. ▼Toxicity

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Species: Daphnia, Daphnia magna

Duration: 48 hours
Test: EL0
Result: 1000 mg/L

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Species: Fish, Oncorhynchus mykiss

Duration: 96 hours
Test: LL0
Result: 1000 mg/L

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Species: Algae, Pseudokirchneriella subcapitata

Duration: 72 hours Test: EL0



Result: 1000 mg/L

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Species: Algae, Pseudokirchneriella subcapitata

Duration: 72 hours
Test: EL50
Result: >1 mg/L

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Species: Daphnia, Daphnia magna

Duration: 48 hours
Test: EL50
Result: 1,4 mg/L

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Species: Fish
Duration: 96 hours
Test: LL50
Result: 2-5 mg/L

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Species: Algae, Pseudokirchneriella subcapitata

Duration: 72 hours
Test: NOELR
Result: 1 mg/L

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Species: Daphnia, Daphnia magna

Duration: 21 days
Test: NOELR
Result: 0,48 mg/L

Product/substance Polyolefin alkyl phenol alkyl amine

Species: Algae
Duration: 96 hours
Test: EC50
Result: 5,4 mg/L

Product/substance Polyolefin alkyl phenol alkyl amine

Species: Algae
Duration: 96 hours
Test: NOEC
Result: 3,65 mg/L

Product/substance Polyolefin alkyl phenol alkyl amine

Species: Daphnia, Daphnia magna

Duration: 21 days
Test: NOEC
Result: 3,38 mg/L

Product/substance 1,2,4-trimethylbenzene Species: Daphnia, Daphnia magna

Duration: 48 hours
Test: LC50
Result: 3,6 mg/L

Product/substance 1,2,4-trimethylbenzene
Species: Fish, Pimephales promelas

 Duration:
 96 hours

 Test:
 LC50

 Result:
 7,72 mg/L

Product/substance naphthalene



Species: Algae, Pseudokirchneriella subcapitata

Duration: 96 hours
Test: EC50
Result: 2,96 mg/L

Product/substance naphthalene

Species: Daphnia, Daphnia magna

Duration: 48 hours
Test: EC50
Result: 2,16 mg/L

Product/substance

Species: Fish, Oncorhynchus gorbuscha

Duration: 96 hours
Test: LC50
Result: 0,96 mg/L

Product/substance

naphthalene

naphthalene

Species: Daphnia, Daphnia pulex

Duration: 125 days
Test: NOEC
Result: 0,59 mg/L

Product/substance

naphthalene

Species: Fish, Oncorhynchus gorbuscha

Duration: 40 days
Test: NOEC
Result: 0,12 mg/L

Product/substance mesitylene;1,3,5-trimethylbenzene Species: Algae, Desmodesmus subspicatus

Duration: 48 hours
Test: EL50
Result: 53 mg/L

Product/substance mesitylene;1,3,5-trimethylbenzene

Species: Daphnia, Daphnia magna

Duration: 48 hours
Test: LL50
Result: 6 mg/L

Product/substance mesitylene;1,3,5-trimethylbenzene

Species: Fish, Carassius auratus

Duration: 96 hours
Test: LL50
Result: 12,52 mg/L

Product/substance mesitylene;1,3,5-trimethylbenzene Species: Algae, Desmodesmus subspicatus

Duration: 48 hours
Test: EL10
Result: 16 mg/L

Product/substance mesitylene;1,3,5-trimethylbenzene

Species: Daphnia, Daphnia magna

Duration: 21 days
Test: NOEC
Result: 0,4 mg/L

Product/substance Diethylbenzene

Species: Algae, Pseudokirchneriella subcapitata

Duration: 72 hours Test: EC50



Result: 1,21 mg/L

Product/substance Diethylbenzene

Daphnia, Daphnia magna Species:

Duration: 48 hours Test: EC50 Result: 2,01 mg/L

Product/substance Diethylbenzene

Species: Fish, Oncorhynchus mykiss

Duration: 96 hours LC50 Test: Result: 0,673 mg/L

Product/substance Diethylbenzene Bacteria Species: Duration: 3 hours Test: NOEC Result: >1000 mg/L

Product/substance Diethylbenzene

Algae, Pseudokirchneriella subcapitata Species:

Duration: 72 hours NOEC Test: Result: 0,547 mg/L

propylbenzene;cumene Product/substance

Algae, Desmodesmus subspicatus Species:

Duration: 72 hours Test: EC50 Result: 2,01 mg/L

Product/substance

propylbenzene;cumene Daphnia, Daphnia magna Species:

Duration: 48 hours Test: FC50

Result: 2,14 mg/L

Product/substance propylbenzene;cumene

Bacteria Species: Duration: 3 hours Test: EL50 Result: >2000 mg/L

Product/substance propylbenzene;cumene

Species: Algae, Desmodesmus subspicatus

Duration: 72 hours EC10 Test: Result: 1,35 mg/L

Product/substance propylbenzene;cumene Species: Daphnia, Daphnia magna

Duration: 21 days Test: NOEC Result: 0,35 mg/L

Product/substance propylbenzene;cumene Fish, Danio rerio Species:

Duration: 28 days Test: NOEC Result: 0,38 mg/L

Product/substance propylbenzene;cumene



Fish, Pimephales promelas Species:

28 days Duration: Test: NOEC 0,38 mg/L Result:

## 12.2. ▼ Persistence and degradability

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradable: Yes **OECD 301 F** Test method: Result: >60%

Product/substance Polyolefin alkyl phenol alkyl amine

Biodegradable:

OECD 301 D Test method:

Result: 4 % - Not readily - 28 days

Product/substance naphthalene

Biodegradable:

Test method:

Result: 0 to 2 % - Not readily - 28 days

Product/substance mesitylene;1,3,5-trimethylbenzene

Biodegradable:

Test method:

Result: 42% 28 days

Product/substance Diethylbenzene

Biodegradable:

Test method: OECD 301 B Result: 4.7 % - 28 days

Product/substance propylbenzene;cumene

Biodegradable:

Test method:

Result: 70% 28 days

#### 12.3. ▼ Bioaccumulative potential

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene

Test method:

Potential bioaccumulation: Yes LogPow: 2,8-6,5 BCF: 99-5780

Other information:

Product/substance 1,2,4-trimethylbenzene

Test method:

Potential bioaccumulation: No data available.

LogPow: 3,63 BCF: 243

Other information:

Product/substance naphthalene

Test method:

Potential bioaccumulation: No data available.

36.5-168 LogPow: BCF: 3,4

Other information:

Product/substance mesitylene;1,3,5-trimethylbenzene

Test method:

Potential bioaccumulation: No data available.

LogPow: 3.42 BCF: 161

Other information:



Product/substance Diethylbenzene

Test method:

Potential bioaccumulation: No data available. LogPow: No data available.

BCF: 320-629

Other information:

Product/substance propylbenzene;cumene

Test method:

Potential bioaccumulation: No data available.

LogPow: 3,55 BCF: 35,48

Other information:

#### 12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

## 12.6. ▼Endocrine disrupting properties

Not applicable.

#### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

13 07 03\* Other fuels (including mixtures)

## Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

#### **SECTION 14: Transport information**

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 14.5 Other PG* Env** information:
ADR	-	-	
IMDG		-	
IATA		-	

<sup>\*</sup> Packing group

#### \*\* Environmental hazards

## Additional information

Not dangerous goods according to ADR, IATA and IMDG.

## 14.6. Special precautions for user

Not applicable.

## 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical



precautions or design of the workplace needed to eliminate exposure, must be considered.

## Demands for specific education

No specific requirements.

## SEVESO - Categories / dangerous substances

Not applicable.

## Additional information

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

#### Sources

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

## 15.2. Chemical safety assessment

No

#### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H226, Flammable liquid and vapour.

H228, Flammable solid.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

H351, Suspected of causing cancer.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

H412, Harmful to aquatic life with long lasting effects.

## The full text of identified uses as mentioned in section 1

= Additives to petrol or diesel fuel

## Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)



OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

**UN = United Nations** 

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

## Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

#### ▼ The safety data sheet is validated by

**Product Safety Department** 

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en