

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** JLM Injector Loosener
- **Article number:** J04210
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 JLM Lubricants B.V.  
 Schiphol Boulevard 127  
 1118 BG Schiphol  
 The Netherlands  
 Tel: +31 (0) 20 201 4995
- **Further information obtainable from:** Research & Development: info@jlm lubricant.com
- **1.4 Emergency telephone number:** During normal business hours: Tel: +31 (0) 202014995

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1                      H222-H229    Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02    GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
 Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
- **Hazard statements**  
 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
 H315            Causes skin irritation.  
 H319            Causes serious eye irritation.  
 H412            Harmful to aquatic life with long lasting effects.
- **Precautionary statements**  
 P101            If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

**Trade name: JLM Injector Loosener**

(Contd. of page 1)

- P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves / eye protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P403 Store in a well-ventilated place.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards****Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**· **Description:** Active substance with propellant**Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-<50%
EC number: 926-141-6 Reg.nr.: 01-2119456620-43	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Asp. Tox. 1, H304	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 95-38-5 EINECS: 202-414-9 Reg.nr.: 01-2119777867-13	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol STOT RE 2, H373; Skin Corr. 1C, H314; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302	≥0.25-<1%

**Additional information:**

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in chapter 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** Generally the product does not irritate the skin.· **After eye contact:** Rinse opened eye for several minutes under running water.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

**Trade name: JLM Injector Loosener**

(Contd. of page 2)

- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Water haze  
Fire-extinguishing powder  
Carbon dioxide  
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**  
Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

Trade name: JLM Injector Loosener

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· **Additional information about design of technical facilities:** No further data; see item 7.

#### · **Ingredients with limit values that require monitoring at the workplace:**

##### 106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

##### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

RCP-TGG	Short-term value: 1200 mg/m <sup>3</sup> , 165 ppm
---------	--

##### 74-98-6 propane

OEL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm Additioneel ingevuld tbv klant voor Hfdst3 SDS
-----	--

##### 75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)

OEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm Additioneel ingevuld obv klant voor Hfdst 3 SDS
-----	---

#### · DNELs

##### 95-38-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol

Dermal	DNEL Long term-systemic	0.06 mg/kg bw/day (Worker)
	DNEL Long term-local	2 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-systemic	14 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	0.46 mg/m <sup>3</sup> (Worker)

#### · PNECs

##### 95-38-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol

PNEC Freshwater	0.00003 mg/l (Undefined)
PNEC Marine water	0.000003 mg/l (Undefined)
PNEC Freshwater sediment	0.376 mg/l(dry weight) (Undefined)
PNEC Sewage Treatment Plant	0.27 mg/l (Undefined)
PNEC Marine water sediment	0.0376 mg/l(dry weight) (Undefined)

· **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

##### · **Personal protective equipment:**

##### · **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

General ventilation

##### · **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

##### · **Protection of hands:**



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

##### · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

Trade name: JLM Injector Loosener

(Contd. of page 4)

application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5$  mm

- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Safety glasses



Tightly sealed goggles

- **Body protection:**

Use protective suit. (EN-13034/6)

Full skin covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&amp;EN ISO 13688; EN13034-6).

- **Limitation and supervision of exposure into the environment**

Use a suitable container to prevent environmental contamination.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

<b>Form:</b>	Aerosol
--------------	---------

<b>Colour:</b>	Colourless
----------------	------------

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
--------------------------------------	---------------

<b>Initial boiling point and boiling range:</b>	-44.5 °C
---	----------

- **Flash point:** -97 °C

- **Flammability (solid, gas):** Not applicable.

- **Auto-ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

<b>Lower:</b>	0.5 Vol %
---------------	-----------

<b>Upper:</b>	10.9 Vol %
---------------	------------

- **Vapour pressure at 20 °C:** 5500 hPa

- **Density at 20 °C:** ~0.6 g/cm<sup>3</sup>

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not applicable.

- **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

- **Partition coefficient: n-octanol/water:** Not determined.

- **Viscosity:**

<b>Dynamic:</b>	Not determined
-----------------	----------------

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

Trade name: JLM Injector Loosener

(Contd. of page 5)

<b>Kinematic:</b>	Not determined.
<b>Solvent content:</b>	
<b>Organic solvents:</b>	95.0 %
<b>Solids content:</b>	2.6 %

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rabbit)
Inhalative	LC50 (8h)	>5000 mg/m <sup>3</sup> (Rat) (Acute Inhalation Toxicity)

##### 95-38-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol

Oral	LD50	1265 mg/kg (Rat)
------	------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

EL0 (48h)	1000 mg/l (Daphnia magna)
EL0 (72h)	1000 mg/l (Pseudokirchneriella subcapitata)
LL0 (96h)	1000 mg/l (Onc)

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

Trade name: JLM Injector Loosener

(Contd. of page 6)

**95-38-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol**


EC50 (72h)	0.03 mg/l (Desmodesmus subspicatus)
LC50 (96h)	0.3 mg/l (Brachydanio rerio)
EC50 (48h)	0.136 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** Not easily biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- **14.1 UN-Number**
- **ADR, ADN, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR, ADN** UN1950 AEROSOLS
- **IMDG** AEROSOLS (2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol), MARINE POLLUTANT
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2.5F Gases.
- **Label** 2.1

(Contd. on page 8)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

Trade name: JLM Injector Loosener

(Contd. of page 7)

· **ADN**  
 · **ADN/R Class:** 2 5F

· **IMDG**

· **Class** 2.1  
 · **Label** 2.1

· **IATA**

· **Class** 2.1  
 · **Label** 2.1

· **14.4 Packing group**  
 · **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances:  
 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol  
 · **Marine pollutant:** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Gases.  
 · **Hazard identification number (Kemler code):** -  
 · **EMS Number:** F-D,S-U  
 · **Segregation groups** Alkalies  
 SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
 · **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
 For AEROSOLS with a capacity above 1 litre:  
 Segregation as for the appropriate subdivision of class 2.  
 For WASTE AEROSOLS:  
 Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
 · **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity  
 · **Transport category** 2  
 · **Tunnel restriction code** D

· **IMDG**  
 · **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

Trade name: JLM Injector Loosener

(Contd. of page 8)

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

#### · National regulations:

#### · Breakdown regulations:

Class	Share in %
NK	75-<100

- VOC-CH 95.01 %
- VOC-EU ~570.0 g/l
- Danish MAL Code 3-1
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

#### · Contact: G.Groot

#### · Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 16.04.2021

Revision: 16.04.2021

**Trade name: JLM Injector Loosener**

(Contd. of page 9)

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3  
· **\* Data compared to the previous version altered. \***

GB

